

for alumina powder KMS92 were determined using simple diametral and axial compression and uniaxial compaction tests in an instrumented die. The results demonstrate that the method can give accurate values for model parameters.

References

- [1] H. Kashani Zadeh, Finite element analysis and experimental study of metal powder compaction, PhD Thesis, Queen's University, 2010.
- [2] C. Lu, Determination of cap model parameters using numerical optimization method for powder compaction, PhD Thesis, Marquette University, 2010.
- [3] K. Kim, S. Choi, H. Park, Densification behavior of ceramic powder under cold compaction, *Transactions-American Society of Mechanical engineers Journal of Engineering Materials and Technology*, 122(2) (2000) 238-244.
- [4] R. Henderson, B. Moriarty, Finite element modelling of decompression after isostatic pressing, *Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture*, 216(2) (2002) 215-224.
- [5] Y. Foo, Y. Sheng, B. Briscoe, An experimental and numerical study of the compaction of alumina agglomerates, *International journal of solids and structures*, 41(21) (2004) 5929-5943.
- [6] P. Carlone, G. Palazzo, Computational modeling of the cold compaction of ceramic powders, *International Applied Mechanics*, 42(10) (2006) 1195-1201.

