

Point to Point Control of a Liquid Carrying Quadrotor

Ali Soltani*, AmirHusain Vahidi Bajestani, Mohammad Goharkhah

Faculty of Mechanical Engineering, Sahand University of Technology

ABSTRACT

Liquid transport by UAVs is a necessary task in autonomous firefighting and field spraying missions. On the other hand, transient and residual sloshing of the liquid during and after the movement can cause instability, increase position error and control effort and create danger or damage if the liquid is flammable. Therefore, in this study, control of a liquid carrier quadrotor has been studied and a controller has been presented that, unlike previous studies, can provide stability in point-to-point transmission without the need to measure or estimate liquid states. For this purpose, a controller is first designed by linearizing the equations of motion of the system and assuming the liquid is rigid via pole placement. On the other hand, in order for the behavior of the system to be similar to the behavior of the design model and to maintain the stability of the system, the liquid sloshing must be reduced as much as possible. Therefore, a command smoother based on the natural frequencies of the liquid sloshing modes is used. The ability of the proposed control system has been investigated, validated and compared with a similar study by simulation. Also, the simulation results show that implementation of the designed command smoother can significantly reduce the amplitude of liquid sloshing, the deviation of the system states from the equilibrium state and the control effort.

KEYWORDS

Quadrotor, Point to point transport, Pole placement, Command smoother.

Introduction

Quadrotors have been among the main interests of scientists due to traits such as high maneuverability, the ability to hover, and vertical take-off and landing[1]. This has caused quadrotor's field of application to expand greatly. Today, some applications such as agricultural drones, refueling drones, and firefighting drones may demand quadrotor to carry a certain amount of liquid on board. However as useful as it can be, liquid carrying quadrotors face many difficulties, one of which being the sloshing effect of the on board liquid. The vibrations caused by the sloshing of the on board liquid can affect the flight dynamics of the quadrotor and potentially can cause the drone to become unstable[2].

Many studies have been made on the case of suppressing liquid slosh. One approach is to implement passive methods which involve using baffles in liquid containers[3]. However, a study showed that using baffles is not capable of fully suppressing liquid sloshing[4]. Thus, using an active approach is much more suitable. One active method of suppressing liquid sloshing is to use open-

* Corresponding Author: Email: asoltani@sut.ac.ir

loop schemes which involve generating a suitable trajectory that does not agitate the on board liquid. Command smoothing is one of such schemes which involves filtering the desired trajectory from frequencies that can excite the sloshing modes. Zang et al. [5] showed that using command smoother to suppress liquid sloshing in containers is very effective.

The main purpose of this paper is to reduce the liquid sloshing while controlling the position of a liquid carrying quadrotor. The combined mathematical model of the liquid and drone were derived using Lagrange equations. This was done while the liquid was modeled as an infinite number of mass-spring-damper. A linear feedback position controller was designed based on the linearized equations of motion. A command smoother was designed based on the first natural frequency of the liquid sloshing to filter the desired command of the controller. In order to confirm the ability of the designed controller and command smoother in reducing the sloshing effects while maintaining the desired values for quadrotor position, a simulation of the derived equations of motion was done using a combination of step inputs for the desired trajectory. Then, the results of current simulation were compared to the results of another control scheme which was implemented on a liquid carrying quadrotor. The results of the simulation showed that the presented method can successfully reduce the sloshing effects of the on board liquid while showing an acceptable performance on trajectory tracking. The results also showed that by reducing the sloshing effects of the liquid, the amount of control input to the system is reduced as well.

Methodology

The equations of motion for the liquid carrying quadrotor were derived using Lagrange equations. Assuming small amplitudes of slosh, the liquid can be modeled as an infinite number of mass-spring-dampers[6]. The controller used to track the desired trajectory was designed based on a linear feedback scheme. In order to derive the control rule, the equations of motion had to be linearized around the hover point of the drone. In designing the controller, it was also assumed that the liquid is a solid mass. Controller gains were chosen such that the controller shows desirable trajectory tracking performance and the dominant poles of the closed loop system become less than the first natural frequency of the liquid slosh. This way the controller is less likely to excite vibration modes of liquid. In order to suppress the sloshing effects of the liquid, a command smoother was designed based on the one presented in [7]. It uses the first natural frequency of the liquid sloshing and filters all frequencies higher than the first natural frequency. This way, the smoothed command does not excite higher frequencies of liquid sloshing. The command smoother is implemented by putting it before the controller, such that the desired control command is first filtered by the command smoother, then goes through the controller.

Results and Discussion

The simulations were done using a set of step inputs for desired trajectory. The results were also compared with another controller which was used to control a liquid carrying quadrotor in [8]. The referenced controller was tuned in a way that the step response of the presented controller and the referenced controller are similar. Using the command smoother caused a small delay in the trajectory tracking performance of the controller. The command smoother was successful at reducing the liquid sloshing while the controller presented in [8], while successful at tracking the desired trajectory, caused a great amount of liquid sloshing. The controller presented in [8] also caused a great spike in control inputs which is undesirable. While, the command smoother reduced the amount control input by suppressing liquid slosh.

Conclusion

The main goal of this study was to reduce the sloshing in liquid carrying quadrotor using command smoother as an open-loop active scheme. The equations of motion were derived using Lagrange equations and a linear feedback controller was designed based on linearized equations of motion. The results of the simulation showed that the command smoother was successful at reducing the amount liquid slosh. This reduction in slosh however, comes with a small delay in tracking performance. This small cost is acceptable, because reducing the amount of liquid slosh can be much more valuable in some cases. Also, command smoother was able to reduce the amount control input by reducing the liquid slosh. This can be very valuable as well, since such drone rely heavily on limited energy storage.

References

- [1] R. Amin, L. Aijun, S. Band, A Review of Quadrotor UAV: Control Methodologies and Performance Evaluation, *International Journal of Automation and Control*, 10(2) (2015) 87-103.
- [2] Y. Zang, Z. Zhou, X. Gu, R. Jiang, L. Kong, X. He, X. Luo, Y. Lan, Design and anti-sway performance testing of pesticide tanks in spraying UAVs, *International Journal of Agricultural and Biological Engineering*, 12 (2019) 10-16.
- [3] H. Qin, L. Mu, W. Tang, Z. Hu, Numerical study on structural response of anti-sloshing baffles of different configurations in a sloshing tank considering hydroelasticity, *Ocean Engineering*, 188 (2019) 1-22.
- [4] B. Naseri Soufiani, M.A. Adli, An expanded impedance control scheme for slosh-free liquid transfer by a dual-arm cooperative robot, *Journal of Vibration and Control*, 27(23-24) (2020) 2793-2806.
- [5] Q. Zang, J. Huang, Dynamics and Control of Three-Dimensional Slosh in a Moving Rectangular Liquid Container Undergoing Planar Excitations, *IEEE Transactions on Industrial Electronics*, 62(4) (2015) 2309-2318.
- [6] R.A. Ibrahim, *Liquid sloshing dynamics*, Cambridge University Press, 2005.
- [7] X. Xie, J. Huang, Z. Liang, Vibration reduction for flexible systems by command smoothing, *Mechanical Systems and Signal Processing*, 39(1-2) (2013) 461-470.
- [8] S. Lee, D.K. Giri, H. Son, Modeling and control of quadrotor UAV subject to variations in center of gravity and mass, in: 2017 14th International Conference on Ubiquitous Robots and Ambient Intelligence (URAI), 2017, pp. 85-90.